

DOLBI

LED Track Light



DALI | ON/OFF




Wattage Range : **12W - 36W**
 Lumen Range : **1200 - 3600lm**
 CCT : **2700K-6500K**
 CRI : **80/90**
 IP Rating : **IP20**
 3 Step Macadam
 Material : **Die Cast Aluminium**
 Lifetime : **L70>50,000 hrs**
 Voltage : **DC24V | 220-240V**

Wattage	D	H
12W	60	130
18W	70	160
20W	70	160
30W	90	185
36W	90	185

Optics : 15° | 24° | 38° 60°




Application

Dolbi LED Track Lights are high-performance, adjustable luminaires designed for precise accent and general lighting applications. Engineered with a compact, modern aluminium housing and advanced optical control, the Dolbi track light delivers focused, glare-controlled illumination with excellent color consistency.

Accessories



4-Line Track



6-Line Track



Base

Glare Control



Honey Comb

BR-DO X X X XWX

12W-36W

Recessed Surface

Custom Grey Black White

HC

Narrow Medium Wide

6500K 4000K 3000K 2700K





MOUNTING

The Dolbi range is no longer only available for track mounting but also as a standalone surface mounted fitting which open a new field of applications.

INTEGRATED DRIVER

This family of track-mounted spots are recognised by a special articulated arm which allows 350° adjustment and a 90° tilting and an integrated(DALI dimmable) driver in integriert.

HIGH LUMINOUS INTENSITY

An intergrated plano-convex lens of a superior quality in combination with a high efficient COB LED with a CRI of 90, ensures an incredible high luminous intensity.

FLAWLESS TRANSITION

An ingenious adjustment system ensures a flawless transition of the beam angle of the Dolbi between 15° and 60°. The look of the Dolbi don't change at all during focusing

TECHNICAL DESCRIPTION

With countless different mounting options, sizes and beam angles, Dolbi is perfect for any room design-whether you need precise lighting accents or even background illumination.

Available in **16** colours.

