

Name

Client

Project Name

Type | Quantity



Disclaimer:-

Brighton Lighting manufactures LED technology-based luminaires designed to deliver reliable, high-performance lighting solutions to our customers.

LED technology continues to evolve rapidly. Brighton Lighting closely monitors these developments and may implement improvements or modifications to its luminaires whenever deemed necessary. Therefore, Brighton Lighting reserves the right to revise, modify, or discontinue products listed in this catalogue at its sole discretion without prior notice.


The information contained in this catalogue is provided for general informational purposes only and is based on the data available at the time of publication. No rights may be derived from the information presented. Brighton Lighting makes no representation or warranty regarding the accuracy, completeness, or suitability of the information or products described in this catalogue for any specific application. Brighton Lighting shall not be held liable for any typographical, technical, or printing errors, nor for any damages resulting from the use of information contained in this publication.

All sales transactions are subject to the Brighton Lighting general terms and conditions. This catalogue and the information contained herein may not be reproduced, copied, or distributed without the prior written consent of Brighton Lighting.

Measurement tolerances are generally ±10% for luminous flux data and ±12% for efficacy values unless otherwise stated. CRI measurement tolerance is ±1.5. All measurements have been carried out using white luminaires. Driver efficiency has been calculated based on a reference efficiency of 89%.


As LED technology and performance continue to improve, specifications may change. For the latest technical information, please refer to the official Brighton Lighting website.

Octav
BR-OCT6.830N66B-F, 6W



Product Description	The OCTAV Spike Light provides focused outdoor illumination for landscape highlighting. Ideal for gardens, pathways, trees, façades, and architectural features in residential, hospitality, and commercial applications.
Finish	Black
Dimension	Dia 50mm L 125mm
Wattage	6W
Lumen	600lm
CCT	3000K
CRI	>90
Protection Rating	IP66
Macadam	3 step
Material	Die Cast Aluminium
Lifetime	L70>50,000 hrs
Voltage	220~240VAC
Class	III
Diffuser	Polycarbonate
Ambient Temp [C°]	-20°~45°
Power Factor	$\lambda > .95^{[5]}$ EN55015
THD	< 10%
Weight	0.9 KG
Beam Angle	24°

Photometric



For Detailed Installation instruction, please consult the QR Code.

Values are based on nominal current at a case temperature of 45°C under normal operating conditions. These values are provided for informational purposes only and do not constitute a warranty or guarantee of performance.