

Name _____

Client _____

Project Name _____

Type | Quantity _____



Disclaimer :-

Brighton Lighting manufactures LED technology-based luminaires designed to deliver reliable, high-performance lighting solutions to our customers.

LED technology continues to evolve rapidly. Brighton Lighting closely monitors these developments and may implement improvements or modifications to its luminaires whenever deemed necessary. Therefore, Brighton Lighting reserves the right to revise, modify, or discontinue products listed in this catalogue at its sole discretion without prior notice.



The information contained in this catalogue is provided for general informational purposes only and is based on the data available at the time of publication. No rights may be derived from the information presented. Brighton Lighting makes no representation or warranty regarding the accuracy, completeness, or suitability of the information or products described in this catalogue for any specific application. Brighton Lighting shall not be held liable for any typographical, technical, or printing errors, nor for any damages resulting from the use of information contained in this publication.

All sales transactions are subject to the Brighton Lighting general terms and conditions. This catalogue and the information contained herein may not be reproduced, copied, or distributed without the prior written consent of Brighton Lighting.

Measurement tolerances are generally ±10% for luminous flux data and ±12% for efficacy values unless otherwise stated. CRI measurement tolerance is ±1.5. All measurements have been carried out using white luminaires. Driver efficiency has been calculated based on a reference efficiency of 89%.

As LED technology and performance continue to improve, specifications may change. For the latest technical information, please refer to the official Brighton Lighting website.


Vitra E
BR-VIE15.830F20W-F, 15W



Product Description : The VITRA Diffused Downlight delivers soft, uniform illumination with low glare and excellent visual comfort. Its diffused optics ensure even light distribution, making it ideal for commercial, hospitality, residential, and general indoor applications.

Finish	: White
Reflector	: White
Dimension	: Dia 145mm H 55mm
Cutout	: Dia 130mm
Wattage	: 15W
Lumen	: 1200lm
CCT	: 4000K
CRI	: >80
Protection Rating	: IP20
Macadam	: 3 step
Material	: PC & Aluminium
Lifetime	: L70>50,000 hrs
Voltage	: 220-240V AC
Class	: II
IK Protection	: IK 02
Diffuser	: Polycarbonate
Ambient Temp [C°]	: -20° ~ 45°
Power Factor	: λ > .95 ^[5] EN55015
THD	: < 10%
Weight	: 0.3 KG
DC (mA)	: 350mA
Beam Angle	: Diffused

Photometric



For Detailed Installation instruction, please consult the QR Code.

Values are based on nominal current at a case temperature of 45°C under normal operating conditions. These values are provided for informational purposes only and do not constitute a warranty or guarantee of performance.